

Baremetal Switch

[Home > Products](#)

Products

Switch

[Baremetal Switch](#)[Ethernet Switch](#)

Networking OS

Accessories

AGC7648A

- 48x 10GbE SFP+
- 6x 100GbE SFP28 uplinks
- 1 Out-of-band management port
- 1 RJ45 console port
- 1 USB port
- 1 AC power supply and support N+1 redundancy
- 4 Fan tray modules
- Max. power output 800w

Please contact us or mail to sales@agemasystems.com for product availability

Overview

Specifications

Ports

- 48x 10GbE SFP+ and 6x 100GbE QSFP28 ports
- 1 RJ-45 10/100/1000Mbps out-of-band management port
- 1 RJ-45 console Port
- 1 USB port

Performance

- Switching chip: Broadcom Qumran-MX
- Switching capacity: 800Gbps switching bandwidth
- Jumbo Frame support: Up to 9Kbyte
- MAC Address: Max 750K

Packet Buffer

- 6GB GDDR5
- T-CAM

Processor, Memories & Storage

- Processor: Intel Rangley C2538
- Memory: 8GB DDR3-SDRAM
- SPI-Flash: 16MB
- Storage: 32GB SSD

Power & Fan

- 4 Fan tray modules
- 1 AC power supply and additional PSU required for N+1 redundancy
- Input voltage : AC 100 ~ 240V
- Output voltage: DC 12V
- Max. Power output: 800W

Environmental specifications

- Operating temperature: 0 to 40°C
- Operating relative humidity: 10 to 90% RH
- Storage temperature: -20 to 70°C
- Storage humidity: 5 to 95% RH

Mechanical

- Dimension (WxDxH): 438.5x460x43 mm
- Weight: 8.28 kg

Regulatory Compliance

- Safety: EN 60950-1, UL/CSA 60950-1, IEC 60950-1, CCC
- Emissions: AS/NZS CISPR 22: Class A, ICES-003, Issue Class A, EN 55022: Class A, VCCI Class A, FCC CFR 47 Part 15, Subpart B Class A, CCC
- Immunity: EN 300 386, EN55024, EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 61000-4-3, EN 61000-4-5, EN 61000-4-6, EN61000-4-8, EN61000-4-11
- RoHS: All AG-Series components are EU RoHS compliant

* All specifications and figures are subject to change without prior notice.

[Back to list](#)

[Privacy](#) | [Terms of use](#) | [Sitemap](#)

© 2015 Agema Systems, Inc. All rights reserved. Designed by CSIDEA