

HP FlexFabric 5930 Switch Series



Product overview

The HP FlexFabric 5930 Switch Series is a family of high performance and ultra-low-latency 10GbE and 40GbE top-of-rack (ToR) data center switches. The switch series is part of the HP FlexFabric data center solution, which is a cornerstone of the FlexNetwork architecture.

The FlexFabric 5930 Switch Series is ideally suited for deployment at the aggregation or server access layer of large enterprise data centers, or at the core layer of medium-sized enterprises.

With the increase pace of deploying virtualized applications, adopting software-defined networking, and the and server-to-server traffic, many data centers now require spine and ToR switch innovations that will meet their requirements. The HP FlexFabric 5930 is optimized to meet the increasing requirements for higher-performance server connectivity, convergence of Ethernet and storage traffic, the capability to handle virtual environments, and ultra-low-latency.

A summary of the highlights of the FlexFabric 5930 Switch Series:

- VXLAN VTEP support for virtualized environments
- OpenFlow support for investment protection and SDN environments
- High-density 10GbE and 40GbE for spine-and-leaf deployments
- Unify management of virtual and physical network with VEPA and IMC
- Data center convergence and resiliency with DCB, FC/FCoE, IRF, and TRILL

Features and benefits

Quality of Service (QoS)

- Powerful QoS features
 - Flexible queue scheduling
 - Including Strict Priority (SP), WRR, WDRR, WFQ, SP+WRR, SP+WDRR, SP+WFQ, Configurable Buffer, Time range, Queue Shaping, CAR with 8kbps granularity
 - Packet filtering and remarking
 - Packet filtering at Layer 2 (L2) through Layer 4 (L4); flow classification based on source MAC address, destination MAC address, source IP (IPv4/IPv6) address, destination IP (IPv4/IPv6) address, port, protocol, and VLAN

Data center optimized

- Flexible high port density
 - The HP FlexFabric 5930 Switch Series enables scaling of the server edge with 10GbE and 40GbE spine and ToR deployments to new heights with a high-density 32-port fixed port switch in a 1RU design, a 2 Slot Modular design with Two 40GbE QSFP+ ports and a 4 Slot Design. Support for 10GbE SFP+, 10GBASE-T, Converged Port 1/10GbE or 4/8Gbps Fiber Channel, and 40GbE ports
- High-performance switching
 - Cut-through and nonblocking architecture delivers low latency (1 microsecond for 10GbE) for very demanding enterprise applications; the switch delivers high-performance switching capacity and wire-speed packet forwarding
- Higher scalability
 - The HP Intelligent Resilient Framework (IRF) technology simplifies the architecture of server access networks; up to nine 5930 switches can be combined to deliver unmatched scalability of virtualized access layer switches and flatter two-tier networks using IRF, which reduces cost and complexity
- Advanced modular operating system
 - Comware v7 software's modular design and multiple processes bring native high stability, independent process monitoring, and restart; the OS also allows individual software modules to be upgraded for higher availability and supports enhanced serviceability functions such as hitless software upgrades with single-chassis ISSU
- TRILL, SPB, and EVB/VEPA
 - TRAnsparent Interconnection of Lots of Links (TRILL) is supported including support of TRILL with IRF, TRILL ECMP up to 8 paths. Support for Shortest Path Bridging (IEEE 802.1aq) with ECMP up to 8 paths. Edge Virtual Bridging with Virtual Ethernet Port Aggregator (EVB/VEPA) provides connectivity into the virtual environment for a data center-ready environment.
- Reversible airflow
 - Enhanced for data center hot-cold aisle deployment with reversible airflow—for either front-to-back or back-to-front airflow
- Redundant fans and power supplies
 - Internal redundant and hot-pluggable power supplies and dual fan trays enhance reliability and availability
- Lower OPEX and greener data center
 - Provide reversible airflow and advanced chassis power management
- Data Center Bridging (DCB) protocols
 - Provides support for IEEE 802.1Qbb Priority Flow Control (PFC), Data Center Bridging Exchange (DCBX), IEEE 802.1Qaz Enhanced Transmission Selection (ETS), Explicit Congestion Notification (ECN) for converged FCoE, iSCSI, and RoCE environments.

- FCoE support

Provides support T11 standards-compliant FC-BB-5 Fibre Channel over Ethernet (FCoE), including FCoE Initialization Protocol (FIP), FCP, Fiber Channel enhanced port types VE, TE and VF, NPV, NPIV, Fabric Name Server, RSCN, Login Services, and name-server zoning, per-VSAN Fabric Services, FSPF, Standard Zoning, and Fiber Channel Ping.

- Jumbo frames

With frame sizes of up to 10,000 bytes on Gigabit Ethernet and 10 Gigabit ports, high-performance remote backup and disaster-recovery services are enabled

- VXLAN support

VXLAN Layer 2 gateway support for up to 4k tunnels

Manageability

- Full-featured console

Provides complete control of the switch with a familiar command-line interface (CLI)

- Troubleshooting

- Ingress and egress port monitoring

- Enable network problem solving

- Traceroute and ping

- Enable testing of network connectivity

- Multiple configuration files

Allow multiple configuration files to be stored to a flash image

- sFlow® (RFC 3176)

Provides wire-speed traffic accounting and monitoring

- SNMPv1, v2c, and v3

Facilitate centralized discovery, monitoring, and secure management of networking devices

- Out-of-band interface

Isolates management traffic from user data plane traffic for complete isolation and total reachability, no matter what happens in the data plane

- Remote configuration and management

Delivered through a secure CLI over Telnet and SSH; Role-Based Access Control (RBAC) provides multiple levels of access; Configuration Rollback and multiple configurations on the flash provide ease of operation; remote visibility is provided with sFlow and SNMPv1/v2/v3 and is fully supported in the HP Intelligent Management Center (IMC)

- ISSU and hot patching

Provides hitless software upgrades with single-unit In Services Software Upgrade (ISSU) and hitless patching of the modular operating system

- Autoconfiguration

Provides automatic configuration via DHCP autoconfiguration

- NTP, SNTP, and PTP Support

Synchronize timekeeping among distributed time servers and clients; Support for Network Time Protocol (NTP), Secure Network Time Protocol (SNTP), and Precision Time Protocol (PTP) IEEE 1588v2 (2008)

Resiliency and high availability

- HP IRF technology

Enables a FlexFabric solution to deliver resilient, scalable, and secured data center networks for physical and virtualized environments; groups up to nine 5930 switches in an IRF configuration, allowing them to be configured and managed as a single switch with a single IP address; and simplifies ToR deployment and management, reducing data center deployment and operating expenses

- IEEE 802.1w Rapid Convergence Spanning Tree Protocol

Increases network uptime through faster recovery from failed links

- IEEE 802.1s Multiple Spanning Tree

Provides high link availability in multiple VLAN environments by allowing multiple spanning trees

- Virtual Router Redundancy Protocol (VRRP)

Allows groups of two routers to dynamically back each other up to create highly available routed environments

- Hitless patch upgrades

Allows patches and new service features to be installed without restarting the equipment, increasing network uptime and facilitating maintenance

- Ultrafast protocol convergence (< 50 ms) with standard-based failure detection—Bidirectional Forwarding Detection (BFD)

Enables link connectivity monitoring and reduces network convergence time for RIP, OSPF, BGP, IS-IS, VRRP, MPLS, and IRF

- Device Link Detection Protocol (DLDP)

Monitors link connectivity and shuts down ports at both ends if unidirectional traffic is detected, helping prevent loops in STP-based networks

- Graceful restart

Allows routers to indicate to others their capability to maintain a routing table during a temporary shutdown and significantly reduces convergence times upon recovery; and supports OSPF, BGP, and IS-IS

L2 switching

- MAC-based VLAN

Provides granular control and security; and uses RADIUS to map a MAC address/user to specific VLANs

- Address Resolution Protocol (ARP)

Supports static, dynamic, and reverse ARP and ARP proxy

- IEEE 802.3x Flow Control

Provides intelligent congestion management via PAUSE frames

- Ethernet Link Aggregation

Provides IEEE 802.3ad Link Aggregation of up to 128 groups of 16 ports; and support for LACP, LACP Local Forwarding First, and LACP Short-time provides a fast, resilient environment that is ideal for the data center

- Spanning Tree Protocol (STP)

Supports STP (IEEE 802.1D), Rapid STP (RSTP, IEEE 802.1w), and Multiple STP (MSTP, IEEE 802.1s)

- VLAN support

Provides support for 4,096 VLANs based on the port, MAC address, IPv4 subnet, protocol, and guest VLAN; and supports VLAN mapping

- IGMP support

Provides support for IGMP Snooping, Fast-Leave, and Group-Policy; IPv6 IGMP Snooping provides L2 optimization of multicast traffic

- DHCP support at L2

Provides full DHCP Snooping support for DHCP Snooping Option 82, DHCP Relay Option 82, DHCP Snooping Trust, and DHCP Snooping Item Backup

L3 services

- Address Resolution Protocol (ARP)

Determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by an L2 network

- Dynamic Host Configuration Protocol (DHCP)

Simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets

- Operations, administration and maintenance (OAM) support

Provides support for Connectivity Fault Management (IEEE 802.1AG) and Ethernet in the First Mile (IEEE 802.3AH); and provides additional monitoring that can be used for fast fault detection and recovery

L3 routing

- Virtual Router Redundancy Protocol (VRRP) and VRRP Extended

Allow quick failover of router ports

- Policy-based routing

Makes routing decisions, based on policies set by the network administrator

- Equal-Cost Multipath (ECMP)

Enables multiple equal-cost links in a routing environment to increase link redundancy and scale bandwidth

- L3 IPv4 routing

Provides routing of IPv4 at media speeds; and supports static routes, RIP and RIPv2, OSPF, BGP, and IS-IS

- Open shortest path first (OSPF)

Delivers faster convergence; and uses this link-state routing Interior Gateway Protocol (IGP), which supports ECMP, NSSA, and MD5 authentication, for increased security and graceful restart for faster failure recovery

- Border Gateway Protocol 4 (BGP-4)

Delivers an implementation of the Exterior Gateway Protocol (EGP), utilizing path vectors; uses TCP for enhanced reliability for the route discovery process; reduces bandwidth consumption by advertising only incremental updates; supports extensive policies for increased flexibility; and scales to very large networks

- Intermediate system to intermediate system (IS-IS)

Uses a path-vector IGP, which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)

- Static IPv6 routing

Provides simple manually configured IPv6 routing

- Dual IP stack
Maintains separate stacks for IPv4 and IPv6 to ease the transition from an IPv4-only network to an IPv6-only network design
- Routing Information Protocol next generation (RIPng)
Extends RIPv2 to support IPv6 addressing
- OSPFv3
Provides OSPF support for IPv6
- BGP+
Extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- IS-IS for IPv6
Extends IS-IS to support IPv6 addressing
- IPv6 tunneling
Allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet; supports manually configured, 6-to-4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels; and is an important element for the transition from IPv4 to IPv6
- Policy routing
Allows custom filters for increased performance and security; and supports ACLs, IP prefix, AS paths, community lists, and aggregate policies
- Bidirectional Forwarding Detection (BFD)
Enables link connectivity monitoring and reduces network convergence time for RIP, OSPF, BGP, IS-IS, VRRP, MPLS, and IRF
- Multicast Routing PIM Dense and Sparse modes
Provides robust support of multicast protocols
- L3 IPv6 routing
Provides routing of IPv6 at media speeds; and supports static routing, RIPng, OSPFv3, BGP4+ for IPv6, and IS-ISv6

Additional information

- Green IT and power
Improves energy efficiency through the use of the latest advances in silicon development; and shuts off unused ports and utilizes variable-speed fans, reducing energy costs

Management

- USB support
 - File copy
Allows users to copy switch files to and from a USB flash drive
- Multiple configuration files
Stores easily to the flash image
- SNMPv1, v2c, and v3
Facilitate centralized discovery, monitoring, and secure management of networking devices

- Out-of-band interface
Isolates management traffic from user data plane traffic for complete isolation and total reachability, no matter what happens in the data plane
- Port mirroring
Enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- Remote configuration and management
Is available through a CLI
- IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
Advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications
- sFlow (RFC 3176)
Provides scalable ASIC-based wire-speed network monitoring and accounting with no impact on network performance; this allows network operators to gather a variety of sophisticated network statistics and information for capacity planning and real-time network monitoring purposes
- Command authorization
Leverages RADIUS to link a custom list of CLI commands to an individual network administrator's login; an audit trail documents activity
- Dual flash images
Provides independent primary and secondary operating system files for backup while upgrading
- Command Line Interface (CLI)
Provides a secure, easy-to-use CLI for configuring the module via SSH or a switch console; and provides direct real-time session visibility
- Logging
Provides local and remote logging of events via SNMP (v2c and v3) and syslog; and provides log throttling and log filtering to reduce the number of log events generated
- Management interface control
Provides management access through a modem port and terminal interface, as well as in-band and out-of-band Ethernet ports; and provides access through the terminal interface, telnet, or secure shell (SSH)
- Industry-standard CLI with a hierarchical structure
Reduces training time and expenses; and increases productivity in multivendor installations
- Management security
Restricts access to critical configuration commands; and offers multiple privilege levels with password protection; ACLs provide telnet and SNMP access, while local and remote syslog capabilities allow logging of all access

- Information center

Provides a central repository for system and network information; aggregates all logs, traps, and debugging information generated by the system and maintains them in the order of severity; and sends out the network information to multiple channels based on user-defined rules

- Network management

HP Intelligent Management Center (IMC) centrally configures, updates, monitors, and troubleshoots

- Remote intelligent mirroring

Mirrors ingress/egress ACL-selected traffic from a switch port or VLAN to a local or remote switch port anywhere on the network

Security

- Access control lists (ACLs)

Provide IP Layer 3 filtering based on source/destination IP address/subnet and source/destination TCP/UDP port number

- RADIUS/TACACS+

Eases switch management security administration by using a password authentication server

- Secure shell

Encrypts all transmitted data for secure remote CLI access over IP networks

- IEEE 802.1X and RADIUS network logins

Controls port-based access for authentication and accountability

- Port security

Allows access only to specified MAC addresses, which can be learned or specified by the administrator

Convergence

- LLDP-MED (Media Endpoint Discovery)

Defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones

Warranty and support

- 1-year warranty

Advance hardware replacement with 10-calendar-day delivery (please consult your HP representative for regional support details.)

- Electronic and telephone support

Limited electronic and business-hour telephone support is available from HP for the entire warranty period; to reach our support centers, visit hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, visit hp.com/networking/warrantysummary

- Software releases

To find software for your product, visit hp.com/networking/support; for details on the software releases available with your product purchase, visit hp.com/networking/warrantysummary

HP FlexFabric 5930 Switch Series

Specifications



	HP FlexFabric 5930-32QSFP+ Switch (JG726A)	HP FlexFabric 5930 4-slot Switch (JH179A)	HP FlexFabric 5930 2QSFP+ 2-slot Switch (JH178A)
I/O ports and slots	32 QSFP+ 40GbE ports	4 module slots	2 module slots 2 QSFP+ 40GbE ports
Additional ports and slots	1 RJ-45 serial console port 1 RJ-45 out-of-band management port 1 USB 2.0	1 RJ-45 serial console port 1 RJ-45 out-of-band management port 1 USB 2.0	1 RJ-45 serial console port 1 RJ-45 out-of-band management port 1 USB 2.0
Power supplies	2 power supply slots 1 minimum power supply required (ordered separately)	4 power supply slots 2 minimum power supplies required (ordered separately)	2 power supply slots 1 minimum power supply required (ordered separately)
Fan tray	2 fan tray slots The customer must order fan trays, as fan trays are not included with the switch. This system requires two same-direction airflow fan trays to function properly. The system should not be operated with only one fan tray for more than 24 hours. The system should not be operated without a fan tray for more than two minutes. The system should not be operated outside of the temperature range of 32°F (0°C) to 113°F (45°C). Failure to comply with these operating requirements may void the product warranty.	2 fan tray slots The customer must order fan trays, as fan trays are not included with the switch. This system requires two same-direction airflow fan trays to function properly. The system should not be operated with only one fan tray for more than 24 hours. The system should not be operated without a fan tray for more than two minutes. The system should not be operated outside of the temperature range of 32°F (0°C) to 113°F (45°C). Failure to comply with these operating requirements may void the product warranty.	2 fan tray slots The customer must order fan trays, as fan trays are not included with the switch. This system requires two same-direction airflow fan trays to function properly. The system should not be operated with only one fan tray for more than 24 hours. The system should not be operated without a fan tray for more than two minutes. The system should not be operated outside of the temperature range of 32°F (0°C) to 113°F (45°C). Failure to comply with these operating requirements may void the product warranty.
Physical characteristics			
Dimensions	17.32(w) x 25.98(d) x 1.72(h) in. (44.00 x 66.0 x 4.36 cm)	17.32(w) x 25.98(d) x 3.47(h) in. (44.00 x 66.0 x 8.81 cm) (2U height)	17.32(w) x 25.98(d) x 1.74(h) in. (44.00 x 66.0 x 4.42 cm) (1U height)
Weight	35.27 lb (16 kg) shipping weight	66.14 lb (30 kg) shipping weight	39.68 lb (18 kg) shipping weight
Full configuration weight	28.66 lb (13 kg)	59.52 lb (27 kg)	35.27 lb (16 kg)
Memory and processor	1 GB flash; Packet buffer size: 12.2 MB, 4 GB SDRAM	1 GB flash; Packet buffer size: 12.2 MB, 4 GB SDRAM	1 GB flash; Packet buffer size: 12.2 MB, 4 GB SDRAM
Performance			
10 Gbps Latency	< 1 μs (64-byte packets)	< 1 μs (64-byte packets)	< 1 μs (64-byte packets)
Throughput	up to 1429 Mpps	up to 1429 Mpps	up to 1071 Mpps
Routing/Switching capacity	2560 Gbps	2560 Gbps	1440 Gbps
Routing table size	120000 entries (IPv4), 60000 entries (IPv6)	120000 entries (IPv4), 60000 entries (IPv6)	120000 entries (IPv4), 60000 entries (IPv6)
MAC address table size	288000 entries	288000 entries	288000 entries
Reliability			
MTBF (years)	37.5	35.8	47.2
MTTR (hours)	1	1	1
Environment			
Operating temperature	32°F to 113°F (0°C to 45°C)	32°F to 113°F (0°C to 45°C)	32°F to 113°F (0°C to 45°C)
Operating relative humidity	10% to 95%, noncondensing	10% to 90%, noncondensing	10% to 90%, noncondensing
Acoustic	Low-speed fan: 59.8 dB, High-speed fan: 74.4 dB	Low-speed fan: 59.8 dB, High-speed fan: 74.4 dB	Low-speed fan: 59.8 dB, High-speed fan: 74.4 dB

	HP FlexFabric 5930-32QSFP+ Switch (JG726A)	HP FlexFabric 5930 4-slot Switch (JH179A)	HP FlexFabric 5930 2QSFP+ 2-slot Switch (JH178A)
Electrical characteristics			
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Maximum heat dissipation	597/1361 BTU/hr (629.83/1435.86 kJ/hr)	474/3030 BTU/hr (500.07/3196.65 kJ/hr)	358/1733 BTU/hr (377.69/1828.31 kJ/hr)
Voltage	90–264 VAC, rated -40 to -75 VDC, rated (depending on power supply chosen)	90–264 VAC, rated -40 to -75 VDC, rated (depending on power supply chosen)	90–264 VAC, rated -40 to -75 VDC, rated (depending on power supply chosen)
Maximum power rating	399 W	888 W	508 W
Idle power	175 W	139 W	105 W
	Notes Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; ROHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; ROHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; ROHS Compliance
Emissions	VCCI Class A; EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; AS/NZS CISPR 22 Class A; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	VCCI Class A; EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; AS/NZS CISPR 22 Class A; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	VCCI Class A; EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; AS/NZS CISPR 22 Class A; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A
Immunity			
Generic	ETSI EN 300 386 V1.3.3	ETSI EN 300 386 V1.3.3	ETSI EN 300 386 V1.3.3
EN	EN 55024:1998+ A1:2001 + A2:2003	EN 55024:1998+ A1:2001 + A2:2003	EN 55024:1998+ A1:2001 + A2:2003
ESD	EN 61000-4-2; IEC 61000-4-2	EN 61000-4-2; IEC 61000-4-2	EN 61000-4-2; IEC 61000-4-2
Radiated	EN 61000-4-3; IEC 61000-4-3	EN 61000-4-3; IEC 61000-4-3	EN 61000-4-3; IEC 61000-4-3
EFT/Burst	EN 61000-4-4; IEC 61000-4-4	EN 61000-4-4; IEC 61000-4-4	EN 61000-4-4; IEC 61000-4-4
Surge	EN 61000-4-5; IEC 61000-4-5	EN 61000-4-5; IEC 61000-4-5	EN 61000-4-5; IEC 61000-4-5
Conducted	EN 61000-4-6; IEC 61000-4-6	EN 61000-4-6; IEC 61000-4-6	EN 61000-4-6; IEC 61000-4-6
Power frequency magnetic field	IEC 61000-4-8; EN 61000-4-8	IEC 61000-4-8; EN 61000-4-8	IEC 61000-4-8; EN 61000-4-8
Voltage dips and interruptions	EN 61000-4-11; IEC 61000-4-11	EN 61000-4-11; IEC 61000-4-11	EN 61000-4-11; IEC 61000-4-11
Harmonics	EN 61000-3-2, IEC 61000-3-2	EN 61000-3-2, IEC 61000-3-2	EN 61000-3-2, IEC 61000-3-2
Flicker	EN 61000-3-3, IEC 61000-3-3	EN 61000-3-3, IEC 61000-3-3	EN 61000-3-3, IEC 61000-3-3
Management	IMC—Intelligent Management Center; Command-line interface; Out-of-band management; SNMP manager; Telnet; FTP	IMC—Intelligent Management Center; Command-line interface; Out-of-band management; SNMP manager; Telnet; FTP	IMC—Intelligent Management Center; Command-line interface; Out-of-band management; SNMP manager; Telnet; FTP
Notes	The customer must order a power supply, as the device does not come with one. At least one JC680A or JC681A is required.	The customer must order a power supply, as the device does not come with one. At least one JC680A or JC681A is required.	The customer must order a power supply, as the device does not come with one. At least one JC680A or JC681A is required.
Services	Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and Protocols

(applies to all products in series)

BGP	RFC 1163 Border Gateway Protocol (BGP) RFC 1771 BGPv4 RFC 1997 BGP Communities Attribute RFC 2918 Route Refresh Capability	RFC 3392 Capabilities Advertisement with BGP-4 RFC 4271 A Border Gateway Protocol 4 (BGP-4) RFC 4360 BGP Extended Communities Attribute	RFC 4456 BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP) RFC 4760 Multiprotocol Extensions for BGP-4
Device management	RFC 1157 SNMPv1/v2c RFC 1305 NTPv3 RFC 1591 DNS (client) RFC 1902 (SNMPv2)	RFC 1908 (SNMPv1/2 Coexistence) RFC 2573 (SNMPv3 Applications) RFC 2576 (Coexistence between SNMPv1, v2, v3)	Multiple Configuration Files Multiple Software Images SSHv1/SSHv2 Secure Shell TACACS/TACACS+
General protocols	IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3ae 10-Gigabit Ethernet IEEE 802.3ag Ethernet OAM IEEE 802.3ah Ethernet in First Mile over Point to Point Fiber - EFMF IEEE 802.3x Flow Control RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 791 IP RFC 792 ICMP RFC 793 TCP RFC 826 ARP RFC 854 TELNET RFC 856 TELNET RFC 868 Time Protocol RFC 896 Congestion Control in IP/TCP Internetworks RFC 950 Internet Standard Subnetting Procedure RFC 1027 Proxy ARP	RFC 1058 RIPv1 RFC 1091 Telnet Terminal-Type Option RFC 1141 Incremental updating of the Internet checksum RFC 1142 OSI IS-IS Intra-domain Routing Protocol RFC 1191 Path MTU discovery RFC 1213 Management Information Base for Network Management of TCP/IP-based internets RFC 1253 (OSPFv2) RFC 1531 Dynamic Host Configuration Protocol RFC 1533 DHCP Options and BOOTP Vendor Extensions RFC 1534 DHCP/BOOTP Interoperation RFC 1541 DHCP RFC 1591 DNS (client only) RFC 1624 Incremental Internet Checksum RFC 1723 RIPv2 RFC 1812 IPv4 Routing RFC 2030 Simple Network Time Protocol (SNTP) v4 RFC 2131 DHCP RFC 2236 IGMP Snooping RFC 2338 VRRP RFC 2453 RIPv2	RFC 2581 TCP Congestion Control RFC 2644 Directed Broadcast Control RFC 2767 Dual Stacks IPv4 & IPv6 RFC 3046 DHCP Relay Agent Information Option RFC 3768 Virtual Router Redundancy Protocol (VRRP) RFC 4250 The Secure Shell (SSH) Protocol Assigned Numbers RFC 4251 The Secure Shell (SSH) Protocol Architecture RFC 4252 The Secure Shell (SSH) Authentication Protocol RFC 4253 The Secure Shell (SSH) Transport Layer Protocol RFC 4254 The Secure Shell (SSH) Connection Protocol RFC 4364 BGP/MPLS IP Virtual Private Networks (VPNs) RFC 4419 Diffie-Hellman Group Exchange for the Secure Shell (SSH) Transport Layer Protocol RFC 4594 Configuration Guidelines for DiffServ Service Classes RFC 4941 Privacy Extensions for Stateless Address Autoconfiguration in IPv6
IPv6	RFC 2080 RIPng for IPv6 RFC 2460 IPv6 Specification RFC 2461 IPv6 Neighbor Discovery RFC 2462 IPv6 Stateless Address Auto-configuration RFC 2463 ICMPv6	RFC 2464 Transmission of IPv6 over Ethernet Networks RFC 2473 Generic Packet Tunneling in IPv6 RFC 2545 Use of MP-BGP-4 for IPv6 RFC 2563 ICMPv6 RFC 2711 IPv6 Router Alert Option RFC 2740 OSPFv3 for IPv6	RFC 2767 Dual stacks IPv4 & IPv6 RFC 3315 DHCPv6 (client and relay) RFC 4291 IP Version 6 Addressing Architecture RFC 4862 IPv6 Stateless Address Auto-configuration RFC 5095 Deprecation of Type 0 Routing Headers in IPv6
MIBs	RFC 1213 MIB II RFC 1907 SNMPv2 MIB RFC 2571 SNMP Framework MIB RFC 2572 SNMP-MPD MIB	RFC 2573 SNMP-Notification MIB RFC 2573 SNMP-Target MIB RFC 2574 SNMP USM MIB RFC 2737 Entity MIB (Version 2)	RFC 3414 SNMP-User based-SM MIB RFC 3415 SNMP-View based-ACM MIB LLDP-EXT-DOT1-MIB LLDP-EXT-DOT3-MIB LLDP-MIB
Network management		RFC 3164 BSD syslog Protocol	
OSPF	RFC 1587 OSPF NSSA RFC 2328 OSPFv2 RFC 3101 OSPF NSSA RFC 3137 OSPF Stub Router Advertisement	RFC 3623 Graceful OSPF Restart RFC 4577 OSPF as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks (VPNs)	RFC 4811 OSPF Out-of-Band LSDB Resynchronization RFC 4812 OSPF Restart Signaling RFC 4813 OSPF Link-Local Signaling
QoS/CoS	IEEE 802.1p (CoS) RFC 2475 DiffServ Architecture RFC 2597 DiffServ Assured Forwarding (AF)	RFC 3247 Supplemental Information for the New Definition of the EF PHB (Expedited Forwarding Per-Hop Behavior)	RFC 3260 New Terminology and Clarifications for DiffServ
Security	Access Control Lists (ACLs)	SSHv2 Secure Shell	

HP FlexFabric 5930 Switch Series accessories

Transceivers

HP X240 40G QSFP+ to QSFP+ 3m Direct Attach Copper Cable (JG327A)
 HP X240 40G QSFP+ to QSFP+ 5m Direct Attach Copper Cable (JG328A)
 HP X240 40G QSFP+ to 4x10G SFP+ 1m Direct Attach Copper Splitter Cable (JG329A)
 HP X240 40G QSFP+ to 4x10G SFP+ 3m Direct Attach Copper Splitter Cable (JG330A)
 HP X240 40G QSFP+ to 4x10G SFP+ 5m Direct Attach Copper Splitter Cable (JG331A)
 HP X140 40G QSFP+ LC LR4 SM 10km 1310nm Transceiver (JG661A)
 HP X140 40G QSFP+ MPO SR4 Transceiver (JG325B)
 HP X140 40G QSFP+ MPO MM 850nm CSR4 300m Transceiver (JG709A)
 HP X240 10G SFP+ SFP+ 7m Direct Attach Copper Cable (JC784C)
 HP X140 40G CFP LC LR4 10km SM Transceiver (JC857A)
 HP X125 1G SFP LC LH40 1310nm Transceiver (JD061A)
 HP X120 1G SFP LC LH40 1550nm Transceiver (JD062A)
 HP X125 1G SFP LC LH70 Transceiver (JD063B)
 HP X120 1G SFP RJ45 T Transceiver (JD089B)
 HP X130 10G SFP+ LC SR Transceiver (JD092B)
 HP X130 10G SFP+ LC LRM Transceiver (JD093B)
 HP X130 10G SFP+ LC LR Transceiver (JD094B)
 HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable (JD095C)
 HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable (JD096C)
 HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable (JD097C)
 HP X120 1G SFP LC LH100 Transceiver (JD103A)
 HP X130 10G XFP LC ZR Transceiver (JD107A)
 HP X130 10G XFP LC LR Transceiver (JD108B)
 HP X120 1G SFP LC SX Transceiver (JD118B)
 HP X120 1G SFP LC LX Transceiver (JD119B)
 HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable (JG081C)
 HP X130 10G SFP+ LC ER 40km Transceiver (JG234A)
 HP X130 10G SFP+ LC ER 40km Transceiver (JG234A)
 HP X130 10G SFP+ LC LH 80km Transceiver (JG915A)
 HP X240 40G QSFP+ to QSFP+ 1m Direct Attach Copper Cable (JG326A)

Power supply

HP 58x0AF 650W AC Power Supply (JC680A)
 HP 58x0AF 650W DC Power Supply (JC681A)

HP FlexFabric 5930-32QSFP+ Switch (JG726A)

HP X711 Front (port side) to Back (power side) Airflow High Volume Fan Tray (JG552A)
 HP X712 Back (power side) to Front (port side) Airflow High Volume Fan Tray (JG553A)

HP FlexFabric 5930 4-slot Switch (JH179A)

HP 5930 24-port SFP+ and 2-port QSFP+ Module (JH180A)
 HP 5930 24-port SFP+ and 2-port QSFP+ with MacSec Module (JH181A)
 HP 5930 24-port 10GBASE-T and 2-port QSFP+ with MacSec Module (JH182A)
 HP 5930 8-port QSFP+ Module (JH183A)
 HP 5930 24-port Converged Port and 2-port QSFP+ Module (JH184A)
 HP FlexFabric 5930 4-slot Back (Power Side) to Front (Port Side) Airflow Fan Tray (JH185A)
 HP FlexFabric 5930 4-slot Front (Port Side) to Back (Power Side) Airflow Fan Tray (JH186A)

HP FlexFabric 5930 2QSFP+ 2-slot Switch (JH178A)

HP 5930 24-port SFP+ and 2-port QSFP+ Module (JH180A)
 HP 5930 24-port SFP+ and 2-port QSFP+ with MacSec Module (JH181A)
 HP 5930 24-port 10GBASE-T and 2-port QSFP+ with MacSec Module (JH182A)
 HP 5930 8-port QSFP+ Module (JH183A)
 HP 5930 24-port Converged Port and 2-port QSFP+ Module (JH184A)
 HP X711 Front (port side) to Back (power side) Airflow High Volume Fan Tray (JG552A)
 HP X712 Back (power side) to Front (port side) Airflow High Volume Fan Tray (JG553A)

Learn more at
hp.com/networking

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2013, 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

sFlow is a registered trademark of InMon Corp.

4AA5-0039ENW, May 2015, Rev. 1

