

# Whitebox & Solutions

## Whitebox & Solutions

### V350

[Home](#) > [Whitebox & Solutions](#) > [SDN/OpenFlow Switch](#) > [V350](#)

#### Ethernet Switch

- [E580](#)
- [E350](#)
- [E330](#)

#### SDN/OpenFlow Switch

- [V580](#)
- [V350](#)
- [V330](#)
- [V150](#)

#### TAP Switch

- [V580-TAP](#)
- [V350-TAP](#)

#### Route Switch Solutions

- [Metro Ring Networks](#)
- [Data Center Application](#)

#### SDN Switch Solutions

- [DDoS Packet Filtering](#)
- [Load Balance](#)
- [SD-DCI](#)
- [Video Monitoring](#)
- [Dynamic QoS Assurance](#)

#### TAP Switch Solutions

- [TAP Bypass Mode](#)
- [TAP In-line Mode](#)

Centec V350 Series Switches—Designed with Centec's CTC5160, the V350 integrates open source OVS and provides competitive system solutions.

- [Introduction](#)
- [Specification](#)
- [Software Features](#)
- [Applications](#)
- [Ordering Information](#)
- [Documents](#)

#### HARDWARE SPECIFICATION

	V350-48T4X	V350-8TS12X
1000M-BaseT	48	8
Total SPF Ports	-	8
Total SFP+ Ports	4	12
Max 1GbE Ports	52	20
Max 10GbE Ports	4	12
Switching Capability	176Gbps	240Gbps
Throughput	130.95Mpps	178.57Mpps
Switching Mode	Store-Forward	
Latency	2.8us	2.8us
CPU	PowerPC P1010	
Memory	1GB	
Flash	2GB	
Packet Buffer	3MB	
100/1000 Mgmt Ports	1	
RS-232 Serial Ports	1(RJ-45)	
USB	-	
Power Supplies	2(1+1 redundant)	
Fans	3(2+1 redundant)	4(3+1 redundant)
Airflow	F-R	
Size(WxHxD)	44.0 x 4.36 x 35.0 cm (17.5 x 1.73 x 13.8 in.)	44 x 4.36 x 34 cm (17.4 x 1.73 x 13.4 in.)
Typical/Max Power Draw	<65W	<47W
Weight(With one PSU)	4.8kg	5.0kg

#### SOFTWARE SPECIFICATION

Classification	Feature	Sub Feaure	Default profile
Openflow	Controller	Max controller number (Connected and managed at the same time)	3