



Micro-Burst Monitoring

- [Micro-Burst Monitoring, on page 1](#)
- [Guidelines and Limitations for Micro-Burst Monitoring, on page 1](#)
- [Configuring Micro-Burst Detection, on page 3](#)
- [Clearing Micro-Burst Detection, on page 5](#)
- [Verifying Micro-Burst Detection, on page 5](#)
- [Example of Micro-Burst Detection Output, on page 6](#)

Micro-Burst Monitoring

The micro-burst monitoring feature allows you to monitor traffic to detect unexpected data bursts within a very small time window (microseconds). This allows you to detect traffic in the network that are at risk for data loss and for network congestion.

A micro-burst is detected when the buffer utilization in an egress queue rises above the configured rise-threshold (measured in bytes). The burst for the queue ends when the queue buffer utilization falls below the configured fall-threshold (measured in bytes).

The feature provides timestamp and instantaneous buffer utilization information about the various queues where micro-burst monitoring is enabled

Guidelines and Limitations for Micro-Burst Monitoring

The following are the guidelines and limitations for micro-burst monitoring:

- Micro-burst monitoring is not supported on the Cisco Nexus 9508 switch (NX-OS 7.0(3)F3(3)).
- Micro-burst monitoring and detection is supported on Cisco Nexus 9300-FX, Cisco Nexus 9300-FX2, and Cisco Nexus N9K-C9364C switches.
- **show** commands with the **internal** keyword are not supported.
- Micro-burst monitoring is available with TOR switches that contain the Network Forwarding Engine (NFE2). The minimum micro-burst that can be detected is 0.64 microseconds for 1 - 3 queues.

On these switches, micro-burst monitoring is supported on unicast egress queues. It is not supported on multicast, CPU, or span queues.

- Beginning with NX-OS 7.0(3)I5(1), micro-burst monitoring is available on the following TOR switches that contain an Application Spine Engine (ASE2, ASE3) or a Leaf Spine Engine (LSE):

TOR Switch	Measurable Minimum Burst Duration
N9K-C92160YC-X	86 μ sec
N9K-C92304QC	96 μ sec
N9K-C9272Q	96 μ sec
N9K-C9232C	96 μ sec
N9K-C9236C	96 μ sec
N9K-C93180YC-EX	73 μ sec
N9K-C93108TC-EX	78 μ sec

On these switches, micro-burst monitoring is supported on both unicast and multicast egress queues.

In addition, early detection of long bursts is supported. For bursts lasting more than 5 seconds, an early burst start record is displayed after 5 seconds from the start of the burst and is updated when the burst actually ends.



Note On these switches, micro-burst duration is not affected by the number of queues configured.

- On TOR switches that contain a Network Forwarding Engine (NFE2), micro-burst monitoring requires IO FPGA version 0x9 or later.

Beginning with NX-OS 7.0(3)I5(1), micro-burst monitoring on TOR switches that contain an Application Spine Engine (ASE2, ASE3) or a Leaf Spine Engine (LSE) require the following IO FPGA versions:

TOR Switch	IO FPGA Version
N9K-C92160YC-X	0x16 or later
N9K-C92304QC	0x10 or later
N9K-C9272Q	0x15 or later
N9K-C9232C	0x6 or later
N9K-C9236C	0x14 or later
N9K-C93180YC-EX	0x8 or later
N9K-C93108TC-EX	0x9 or later

For more information about EPLD programming to upgrade the FPGA, see the *Cisco Nexus 9000 Series FPGA/EPLD Upgrade Release Notes*.

- The following are guidelines for micro-burst duration on TOR switches that contain a Network Forwarding Engine (NFE2):



Note Micro-burst duration is the duration of the burst that can be detected. For example, when micro-burst monitoring is configured for 1 - 3 queues, micro-bursts that exceed 0.64 microseconds are detected. Increasing the number of queues that are configured for micro-burst monitoring increases the duration of the burst that can be detected.

1 - 3 queues	0.64 microsecond duration
8 queues with 10 ports each	9.0 microsecond duration
10 queues with 132 ports each	140 microsecond (0.14 millisecond) duration

- By default, the switch stores a maximum of 1000 burst records. The maximum number of records is configurable within a range of 200 - 2000 records.
 - At least, 20 burst records are stored for each queue even when the maximum number of burst records has been reached.
 - When the maximum number of burst records has been reached, the oldest record is deleted to allow the storage of a new record.
 - You can use the **hardware qos burst-detect max-records** *number-of-records* command to configure the maximum number of burst records to store.
 - You can use the **show hardware qos burst-detect max-records** command to display the maximum number of burst records that can be stored.
- Too many back to back burst records while traffic is being drained from queues might result in jitter. To avoid jitter, configure the fall-threshold to be less than the rise-threshold. As a best practice, configure the fall-threshold to be approximately 20% of the rise-threshold value (bytes).

Configuring Micro-Burst Detection

You can enable micro-burst detection for all interfaces on the device.

SUMMARY STEPS

1. **configure terminal**
2. **policy-map type queuing** *policy-map-name*
3. **class type queuing** *class-name*
4. **burst-detect rise-threshold** *rise-threshold-bytes* **bytes** **fall-threshold** *fall-threshold-bytes* **bytes**
5. **exit**

DETAILED STEPS

	Command or Action	Purpose				
Step 1	configure terminal Example: <pre>switch# configure terminal switch(config)#</pre>	Enters global configuration mode.				
Step 2	policy-map type queuing <i>policy-map-name</i> Example: <pre>switch(config)# policy-map type queuing xyz switch(config-pmap-que)#</pre>	Configures the policy map of type queuing and then enters policy-map mode for the policy-map name you specify.				
Step 3	class type queuing <i>class-name</i> Example: <pre>switch(config-pmap-que)# class type queuing c-out-def switch(config-pmap-c-que)#</pre>	Configures the class map of type queuing and then enters policy-map class queuing mode.				
Step 4	burst-detect rise-threshold <i>rise-threshold-bytes bytes</i> fall-threshold <i>fall-threshold-bytes bytes</i> Example: <pre>switch(config-pmap-c-que)# burst-detect rise-threshold 208 bytes fall-threshold 208 bytes</pre>	Specifies the rise-threshold and the fall-threshold for micro-burst detection. Note <table border="1" data-bbox="971 1012 1481 1476"> <tbody> <tr> <td>TOR switches with Network Forwarding Engine (NFE2)</td> <td> Range for rise-threshold bytes: 208 - 4194304. Range for fall-threshold bytes: 208 - 4194304. </td> </tr> <tr> <td>TOR switches with Application Spine Engine (ASE2, ASE3) or Leaf Spine Engine (LSE)</td> <td> Range for rise-threshold bytes: 208 - 13319072. Range for fall-threshold bytes: 208 - 13319072. </td> </tr> </tbody> </table>	TOR switches with Network Forwarding Engine (NFE2)	Range for rise-threshold bytes: 208 - 4194304. Range for fall-threshold bytes: 208 - 4194304.	TOR switches with Application Spine Engine (ASE2, ASE3) or Leaf Spine Engine (LSE)	Range for rise-threshold bytes: 208 - 13319072. Range for fall-threshold bytes: 208 - 13319072.
TOR switches with Network Forwarding Engine (NFE2)	Range for rise-threshold bytes: 208 - 4194304. Range for fall-threshold bytes: 208 - 4194304.					
TOR switches with Application Spine Engine (ASE2, ASE3) or Leaf Spine Engine (LSE)	Range for rise-threshold bytes: 208 - 13319072. Range for fall-threshold bytes: 208 - 13319072.					
Step 5	exit Example: <pre>switch(config-pmap-c-que)# exit switch(config)#</pre>	Exits policy-map queue mode.				

Clearing Micro-Burst Detection

You can clear micro-burst detection for all interfaces or a selected interface.

SUMMARY STEPS

1. `clear queuing burst-detect [slot] [interface port [queue queue-id]]`

DETAILED STEPS

	Command or Action	Purpose
Step 1	clear queuing burst-detect [slot] [interface port [queue queue-id]] Example:	Clears micro-burst information from all interfaces or the specified interface.

Example

- Example for an interface:

```
clear queuing burst-detect interface Eth1/2
```

- Example for a queue:

```
clear queuing burst-detect interface Eth1/2 queue 7
```

Verifying Micro-Burst Detection

The following displays micro-burst monitoring information:

Command	Purpose
show queuing burst-detect	Displays micro-burst counters information for all interfaces.

- Example for an interface:

```
show queuing burst-detect interface Eth 1/2
```

- Example for a queue:

```
show queuing burst-detect interface Eth 1/2 queue 7
```

Example of Micro-Burst Detection Output

Example output of TOR switch.

```
belv0# show queuing burst-detect detail
slot 1
=====
```

Microburst Statistics

Flags: E - Early start record, U - Unicast, M - Multicast

Ethernet Intfc	Queue	Start Depth (bytes)	Start Time	Peak Depth (bytes)	Peak Time	End Depth (bytes)	End Time	Duration
Eth1/36	U0	310128	2011/01/11 22:31:51:081725	310128	2011/01/11 22:31:51:081725	0	2011/01/11 22:31:51:081918	193.14 us
Eth1/36	U0	311168	2011/01/11 22:31:51:181765	311168	2011/01/11 22:31:51:181765	0	2011/01/11 22:31:51:181959	193.90 us
Eth1/36	U0	283712	2011/01/11 22:31:51:281825	283712	2011/01/11 22:31:51:281825	0	2011/01/11 22:31:51:282018	193.63 us
Eth1/36	U0	283712	2011/01/11 22:31:51:381862	283712	2011/01/11 22:31:51:381862	0	2011/01/11 22:31:51:382056	193.42 us
Eth1/36	U0	312000	2011/01/11 22:31:51:481885	312000	2011/01/11 22:31:51:481885	0	2011/01/11 22:31:51:482080	194.42 us
Eth1/36	U0	221312	2011/01/11 22:31:51:581974	221312	2011/01/11 22:31:51:581974	0	2011/01/11 22:31:51:582168	193.58 us
Eth1/36	U0	291616	2011/01/11 22:31:51:681964	291616	2011/01/11 22:31:51:681964	0	2011/01/11 22:31:51:682157	193.10 us
Eth1/36	U0	190112	2011/01/11 22:31:51:782067	190112	2011/01/11 22:31:51:782067	18312	2011/01/11 22:31:51:782154	86.22 us
Eth1/36	U0	70512	2011/01/11 22:31:51:882167	70512	2011/01/11 22:31:51:882167	0	2011/01/11 22:31:51:882253	85.74 us
Eth1/36	U0	185328	2011/01/11 22:31:52:082111	185328	2011/01/11 22:31:52:082111	0	2011/01/11 22:31:52:082304	193.09 us
Eth1/36	U0	245856	2011/01/11 22:31:52:182158	245856	2011/01/11 22:31:52:182158	0	2011/01/11 22:31:52:182352	193.34 us
Eth1/36	U0	138112	2011/01/11 22:31:52:282293	138112	2011/01/11 22:31:52:282293	0	2011/01/11 22:31:52:282380	86.53 us
Eth1/36	U0	242112	2011/01/11 22:31:52:382284	242112	2011/01/11 22:31:52:382284	0	2011/01/11 22:31:52:382478	193.55 us
Eth1/36	U0	136448	2011/01/11 22:31:52:482264	195312	2011/01/11 22:31:52:482348	0	2011/01/11 22:31:52:482542	278.16 us
Eth1/36	U0	299312	2011/01/11 22:31:52:582334	299312	2011/01/11 22:31:52:582334	0	2011/01/11 22:31:52:582612	278.12 us
Eth1/36	U0	184912	2011/01/11 22:31:52:682432	184912	2011/01/11 22:31:52:682432	13312	2011/01/11 22:31:52:682517	85.42 us
Eth1/36	U0	148304	2011/01/11 22:31:52:782387	148304	2011/01/11 22:31:52:782387	0	2011/01/11 22:31:52:782580	192.94 us
Eth1/36	U0	226512	2011/01/11 22:31:52:882492	226512	2011/01/11 22:31:52:882492	0	2011/01/11 22:31:52:882685	193.37 us