

# Cell Site Gateway

## AS7315-27X



The Edgecore AS7315-27X is an open cell site gateway platform that is OCP Accepted and TIP DCSG Compliant. AS7315-27X features a combination of 1/10 Gbps, 25 Gbps, and 100 Gbps interfaces with optimized performance by utilizing merchant silicon, and standard x86 processor for access and aggregation networks.

With temperature hardened design, the AS7315-27X is able to operate at wide operational temperature range from -40°C to 65°C and it equipped with redundant/hot swappable power and fan modules that provides high availability and hassle-free maintenance. In particular, AS7315-27X supports stacking option for scalability, and redundancy in resilient network topology.

The AS7315-27X builds in network timing and synchronization functions that makes it ideal solution for current LTE and emerging 5G mobile backhaul network. The AS7315-27X is installed with ONIE (Open Network Install Environment) that provides the freedom of choice for the preferred NOS (Network Operating System) integration.

## Key Features and Benefits


- Open cell site gateway platform for mobile backhaul networks.
- 20 x 1G/10G SFP+, 4 x 1G/10G/25G SFP28 and 3 x 100G QSFP28 fixed ports.
- Full line-rate Layer 2 or Layer 3 forwarding of 300 Gbps.
- High resilience in stacking configuration of two AS7315-27X units
- Support IEEE1588v2 and SyncE functions in hardware
- Rack mountable in standard 19" racks.
- Supports side-to-side airflow SKU.
- All ports and PSUs on front.
- Hot-swappable, load sharing, redundant AC/48VDC PSUs.
- Hot swappable 4+1 redundant fan modules.
- Management: Ethernet and console RJ-45 ports; USB storage port.
- Hardware switch pre-loaded with Open Network Install Environment (ONIE).
- Compatible with Open Network Linux (ONL).



Software Supported



Interfaces



Description			
1	Power Supply	9	GPS antenna port
2	100G QSFP28 port	10	25G SFP28 ports
3	USB storage port	11	10G SFP+ ports
4	100G QSFP28 stacking ports	12	Stack Sync RJ-45 port
5	Stack Control RJ-45 port	13	BITS port
6	TOD RJ-45 port	14	RJ-45 console port
7	Management port (MGMT)	15	Fan Tray
8	Alarm RJ-45 port		

## Ports

- Switch Ports
  - 20 x SFP+ (each supporting 10 GbE or 1 GbE)
  - 4 x SFP28 (each supporting 1GbE, 10 GbE or 25 GbE)
  - 3 x 100G QSFP28 (each supporting 1 x 40/100 GbE or 4 x 10/25 GbE or 2 x 50 GbE)
- Management Ports on Front Panel
  - 1 x RJ-45 serial console
  - 1 x RJ-45 1000BASE-T management Ethernet port (MGMT)
  - 1 x USB
  - 1 alarm I/O
- Clocking and Timing ports
  - Station Clock Input and Output ports
  - PRTC: ITU-T G.8272
  - Pulse-per-Second (PPS) input and output
  - Time-of-Day (TOD) input
  - Integrated GNSS receiver
- Stacking Interface
  - 2 out of 3 100G QSFP28 can be used for stacking
  - 1 x 1 GbE from CPU(control signal)
  - 1 x RJ45 for sync signals
  - Optics and cables for stacking:
    - QSFP28 DAC up to 2 m
    - QSFP28 AOC up to 30 m

## Key Components

- Switch Silicon: Broadcom BCM88470 Qumran-AX, 3 Gbytes of DDR4 memory
- CPU module: COM Express module type 7, Intel ATOM C3508 4 core @ 1.6GHz x86 processor, 16G RAM DDR4-2400
- Stratum 3E compliant oscillator (OCXO)
- SSD M.2, 32 Gbytes

## Performance

- 300 Gbps bidirectional switching capacity
- 300 Mpps packet processing rate
- Scales to 600 Gbps per node in stacked configuration (2 x AS7315-27X)

## Software

- Switch is loaded with Open Network Install Environment (ONIE)
- Compatible with the following NOS options:
  - Open Network Linux (ONL)

## Physical and Environmental

- Dimensions (WxDxH): 440 x 300 x 44 mm
- Weight 5.35 kg (11.79 lb), with two installed PSUs
- Installations to standard 19", 21", 23", and ETSI 600 mm racks or cabinets as well as OCP 21 inch open racks

## PSU

- DC Input : 36V -72V, 10A
- AC Input : 100V-240V, 5A
- Power Consumption :250W( Maximum)

## Regulatory Compliance

- Safety Compatibility
  - EN 62368-1:2014 + AC:2015
  - IEC 62368-1:2014
- Electromagnetic Compatibility
  - EN 300 386 V1.6.1 (2012-09)
- Installation environment: telecommunication center
- ITU-T K.80:07/2009
- FCC 47 CFR Part 15, Subpart B, Class A
- EN 301 489-1 V2.1.1
- EN 301 489-19 V2.1.0
- EN 303 413 V1.1.1
- Radio Equipment Directive 2014/53/EU

## Environmental

- Usage altitude 60 m below sea level (106 kPa air pressure) to 3000 m (70 kPa)
- Storage:
  - IEC60068-2-14
  - Temperature: -40°C to +70°C
- Transportation: ETSI EN 300 019-1-2 Class 2.3
  - Temperature: -40°C to +70°C (-40°F to +158°F)
  - Operating Conditions: [ETSI EN 300 019-1-3] Class 3.2
  - Temperature range: -40°C to +65°C (-40°F to 149°F)
  - Relative humidity: 5% to 95%
- The product complies with the current version of the following EU directives:
  - RoHS
  - WEEE
  - REACH

## Warranty

Please check [www.edge-core.com](http://www.edge-core.com) for the warranty terms in your country.

## For More Information

To find out more about Edgecore Networks Corporation products and solutions, visit [www.edge-core.com](http://www.edge-core.com).

## About Edgecore Networks Corporation

Edgecore Networks Corporation is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edgecore Networks Corporation delivers the software and systems that transform the way the world connects. Edgecore Networks Corporation serves customers and partners worldwide. Additional information can be found at [www.edge-core.com](http://www.edge-core.com).

Edgecore Networks Corporation is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edgecore data center switches are developed and manufactured by Accton.

To purchase Edgecore Networks solutions, please contact your Edgecore Networks Corporation representatives at +886 3 563 8888 (HQ) or +1 (949)-336-6801 or authorized resellers.

© Copyright 2021 Edgecore Networks Corporation. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edgecore Networks Corporation. Edgecore Networks Corporation shall not be liable for technical or editorial errors or omissions contained herein.

## Ordering Information

**Base model: AS7315-27X, 20 x 1G/10G SFP+, 4 x 1G/10G/25G SFP28 and 3 x 100G QSFP28 fixed ports. ONIE software installer.**

Model Number	CPU Module	PSU	Airflow	Region (power cord)
7315-27X-O-AC-S-US	Intel Atom C3508	Dual AC PSUs	Side-to-Side airflow	US
7315-27X-O-AC-S-UK	Intel Atom C3508	Dual AC PSUs	Side-to-Side airflow	UK
7315-27X-O-AC-S-EU	Intel Atom C3508	Dual AC PSUs	Side-to-Side airflow	EU
7315-27X-O-AC-S-JP	Intel Atom C3508	Dual AC PSUs	Side-to-Side airflow	JP
7315-27X-O-48X-S	Intel Atom C3508	Dual DC PSUs	Side-to-Side airflow	N/A

### Field replacement units

Part Number	Model	Description
131700000434A	CRXT-T0T12BS	AS7315-27X DC PSU (Black Housing)
131700000453A	SPAACTN-03BG	AS7315-27X AC PSU (Black Housing)
F0TZZ5627001A	FAN-1U-1x1J-S	AS7315-27X Fan Tray Spare Part