

CSE 201

Homework Assignment 4

1. Recall the n^{th} harmonic number was defined to be $H_n = \sum_{k=1}^n \left(\frac{1}{k}\right) = 1 + \frac{1}{2} + \frac{1}{3} + \cdots + \frac{1}{n-1} + \frac{1}{n}$. Use induction to prove that

$$\sum_{k=1}^n kH_k = \frac{1}{2}n(n+1)H_n - \frac{1}{4}n(n-1)$$

for all $n \geq 1$. (Hint: Use the fact that $H_n = H_{n-1} + \frac{1}{n}$.)

2. Use the results of problem #1 above, and problem #2 on the Midterm 1 Review sheet to show, by direct substitution, that the solution to the recurrence

$$t(n) = (n-1) + \frac{2}{n} \cdot \sum_{k=1}^{n-1} t(k)$$

is given by: $t(n) = 2(n+1)H_n - 4n$.

3. Design a recursive algorithm called $\text{Extrema}(A, p, r)$ that, given an array $A[1 \cdots n]$ finds and returns both the min and max of the subarray $A[p \cdots r]$ as an ordered pair: $(\min(A[p \cdots r]), \max(A[p \cdots r]))$. Your algorithm should perform exactly $\lceil 3n/2 \rceil - 2$ array comparisons on an input array of length n . (Hint: Section 9.1 of the text describes an iterative algorithm that does this.)

- Write your algorithm in pseudo-code.
- Prove the correctness of your algorithm by induction on $m = r - p + 1$, the length of the subarray $A[p \cdots r]$.
- Write a recurrence for the number of comparisons performed on $A[1 \cdots n]$, and show that $T(n) = \lceil 3n/2 \rceil - 2$ is its solution.

4. (This is a re-wording of problem 4.2-4 on page 82 of CLRS 3rd edition.) Determine the largest integer k such that if there is a way to multiply 3×3 matrices using k multiplications (not assuming commutativity of multiplication of matrix elements), then there is an algorithm to multiply $n \times n$ matrices (where n is an exact power of 3) in time $o(n^{\lg(7)})$. What would the run time of this algorithm be? (Hint: Proceed as in the analysis of Strassen's algorithm, but recur on submatrices of size $\frac{n}{3} \times \frac{n}{3}$.)

5. (This is a generalization of problem 4.2-5 on page 82 of CLRS 3rd edition.) Suppose there is a method for multiplying $m \times m$ matrices using only k multiplications (not assuming commutativity of multiplication of matrix elements), where $k < m^3$. Explain how to recursively multiply $n \times n$ matrices (where n is an exact power of m) in time $o(n^3)$ by using this method as a subroutine. What is the runtime of your algorithm? (Hint: Imitate Strassen's algorithm.)

6. (This is a slight re-wording of problem 8-5 on page 207 of CLRS 3rd edition.) Suppose that, instead of sorting an array, we just require that the elements increase on average. More precisely, we call an n -element array $A[1 \cdots n]$ **k -sorted** if for all i in the range $1 \leq i \leq n - k$, the following holds:

$$\frac{\sum_{j=i}^{i+k-1} A[j]}{k} \leq \frac{\sum_{j=i+1}^{i+k} A[j]}{k}$$

- What does it mean for an array to be 1-sorted?
- Give a permutation of the numbers $\{1, 2, 3, \dots, 10\}$ that is 2-sorted, but not sorted.
- Prove that an n -element array is k -sorted if and only if $A[i] \leq A[i + k]$ for all i in the range $1 \leq i \leq n - k$.
- Describe an algorithm that k -sorts an n -element array in time $\Theta(n \log n)$.