

# N5860-48SC Switch

HIGH PERFORMANCE 10GB SWITCH WITH 100GB FOR DATA CENTERS

N5860-48SC leaf switch is ideal for small-sized data centers and cloud computing services, providing stable, reliable and secure Layer 2/Layer 3 switching services.



## Overview

The N5860-48SC leaf switch is ideal for small-sized data centers and cloud computing services. Compact 1U ToR high-density switch with full line-rate 48 1G/10G and 8 40/100G ports, delivering zero packet loss, low latency, non-blocking lossless Ethernet.

The switch incorporates multiple features that optimize data center network flexibility, efficiency, and reliability, including industry-leading chip, redundant hot-swappable power supplies and fans, VXLAN, MLAG, PFC, ECN, etc, meeting the growing demands of data center environment.

## Benefits

- Broadcom BCM56770 Switch Chip
- Low-latency, Zero Packet Loss with PFC/ECN
- VXLAN Scales Data Center Capacity
- MLAG, GR and BFD Enhance Reliability
- 1+1 Redundant Power Supplies
- 3+1 Redundant Fan Modules
- CLI/ SNMPv1/v2c/v3/Telnet

## Product Characteristics

### Non-Blocking Forwarding

Ideal for the next generation data center and cloud computing, the switch is of the line speed products, which conforms to the East-West development trend of traffic in the data center. The switch employs an advanced cache scheduling mechanism to maximize the cache capability of the device, ensuring truly non-blocking transmission in the increasingly demanding data center environment.

### Data Center Virtualization

The N5860-48SC adopts the industry-leading stacking technology to achieve unified network management, reducing network nodes and enhancing network reliability. The failover time for link failure is within 50-200ms to guarantee uninterrupted operation for mission-critical applications. The cross-device link aggregation feature enables access to the server or switch to achieve active-active uplinks.

### Overlay Network Connection

The switch supports VXLAN, which can meet the requirements of overlay network construction in data centers, and solves the problem of insufficient VLAN number and difficult scale expansion of traditional data center networks. Based on the N5860-48SC switch, the basic network can be divided into new subnets without changing the physical topology. At the same time, there is no need to consider the restrictions of physical network IP address and broadcast domain.

### Data Center Layer 2 Network Expansion

Vxlan technology has the ability to build a logical layer-2 network on the basis of L3 network by encapsulating layer-2 message in UDP tunnel message.

The switch supports EVPN protocol and provides VTEP (tunnel terminal) automatic discovery and authentication, which can reduce the flooding of VxLAN data plane and avoid vxlan's dependence on the underlying deployment multicast, simplify the deployment of VxLAN , improve the construction efficiency of layer-2 network, and better meet the deployment requirements of layer-2 network in the data center.

### RDMA-based Lossless Ethernet

The switch implements low-delay forwarding of the lossless Ethernet based on the Remote Direct Memory Access (RDMA) and optimizes service forwarding performance. It greatly reduces the operation cost per bit of the entire network and enhances the competitive edge of service products.

### Carrier-Class Reliability Protection

The switch supports built-in redundant power modules and modularized fan components. All the interface boards, power modules, and fan modules are hot-pluggable to guarantee undisturbed switching operation. In addition, the switch supports fault detection and automatic alarms for the power and fan modules. The rotation speed of the fans automatically adjusts to the ambient temperature. The switch further provides device-level and link-level reliability protection with the over-current, over-voltage, and overheating protection measures.

And it supports the features like Graceful Restart (GR) and Bidirectional Forwarding (BFD) mechanisms. All the features ensure the network convergence time is unaffected even when the network bears abundant services and heavy traffic, and therefore ensure normal operation.

## Flexible and Comprehensive Security Policies

The N5860-48SC features multiple security features, which effectively defend against or control virus flooding and hacker attacks. These features include anti-DoS attack, validity check of ARP packets on ports, and multiple hardware-based ACL policies.

The switch supports hardware-based IPv6 ACLs, which can easily control IPv6 users' access to edge devices even when IPv6 users exist within an IPv4 network. It allows coexistence of IPv4 and IPv6 users on the network and can control access permissions of IPv6 users, such as restricting access to sensitive resources on the network.

The switch adopts industry-leading CPU Protection Policy (CPP) technology, which is an advanced hardware-based CPU protection mechanism, to distinguish data traffic destined to the CPU and process data according to queue priorities. The switch implements bandwidth control to protect the CPU against unauthorized traffic consumption, malicious attacks and resource consumption and hence to ensure switch security. The hardware of the N5860-48SC allows flexible binding of a user IP address or a MAC address to a port or a switch to strictly control user access. The switch supports DHCP snooping, which allows only a DHCP response to a trusted port to prevent spoofing by unauthorized DHCP servers. Based on DHCP snooping, the switch dynamically monitors ARP packets, checks user IP addresses, and directly discards packets that do not comply with the bound entries. The N5860-48SC effectively defends against ARP spoofing and source IP address spoofing.

The switch also supports Telnet access control based on source IP addresses. The measure prevents unauthorized users or hackers from attacking or controlling devices and thereby enhances security of the device NMS. The N5860-48SC also implements Secure Shell (SSH) and SNMP V3 to encrypt management information in Telnet and SNMP processes, thereby ensuring security of management device information and preventing hackers from waging attacks or controlling devices.

The switch prevents unauthorized users from network access through multiple functions. These functions include multi-element binding, port security, time ACL, and bandwidth limit based on data traffic. The N5860-48SC highly strengthens access security and is a perfect match for large-sized networks.

## IPv4/IPv6 Dual-Stack Multi-Layer Switching

The hardware of the N5860-48SC supports line-rate IPv4/IPv6 dual-stack multi-layer switching, and distinguishes and processes IPv4 and IPv6 protocol packets. The switch also supports multiple tunneling technologies including manually configured tunnels, automatic tunnels, ISATAP tunnels and so on. The switch provides flexible IPv6 inter-network communication solutions to be realized according to the requirement plan and status quo of the IPv6 networks. The switch is also applicable to an IPv4-only or IPv6-only network, or a hybrid of IPv4 and IPv6 network, fulfilling the transition requirements from IPv4 to IPv6 network.

The switch supports a wide range of IPv4 routing protocols including static routing, RIP, OSPF, and BGP4, which can be selected flexibly according to the network environment. The series also supports an abundant list of IPv6 routing protocols, such as static routing, RIPng, OSPFv3, and BGP4+, which can be selected flexibly either to upgrade the existing network to IPv6 network or to construct a new IPv6 network.

## Advanced Management

The switch supports a family of management ports such as Console, MGMT and USB. The switch also supports SNMP V1/V2C/V3, a universal network management platform. In addition, the switch console port can be managed via Telnet / SSHv2, HTTP or HTTPS. The switch enables Command Line Interface (CLI), Telnet, and cluster management, which simplify device management and provides various encryption modes such as SSH2.0 to enhance network security.

---

The switch supports SPAN/RSPAN mirroring and multiple mirroring observation ports, offering users high visibility and transparency for easy maintenance. The switches also provide a wide range of network traffic reports to help users optimize network structure and adjust resources deployment accordingly.

## Technical Specification

N5860-48SC switch comes with the industry-standard hardware and FSOS. Here's a look at the details.

### CHARACTERISTICS

|                         | N5860-48SC                  |
|-------------------------|-----------------------------|
| <b>Ports</b>            |                             |
| 1G/10G SFP+             | 48                          |
| 40G/100G QSFP28         | 8                           |
| RJ45 Management Port    | 1                           |
| Console Port            | 1                           |
| USB                     | 1                           |
| <b>Operating System</b> |                             |
| OS                      | FSOS                        |
| <b>Key Components</b>   |                             |
| Switch Chip             | Broadcom BMC56770           |
| CPU                     | Quad-core processor, 1.5GHz |
| SDRAM                   | 4GB                         |
| <b>Performance</b>      |                             |
| Layer Type              | Layer 3                     |
| Switching Capacity      | 2.56 Tbps                   |
| Forwarding Rate         | 1.90 Bpps                   |
| MAC Address             | 96K                         |
| Packet Buffer           | 32MB                        |
| Flash Memory            | 8GB                         |
| Latency                 | <1 $\mu$ s                  |
| Number of VLANs         | 4K                          |
| Jumbo Frame             | 9KB                         |
| Stackability            | Up to 2 Units               |
| MTBF (Hours)            | 330K                        |

## CHARACTERISTICS

|                                     | N5860-48SC   |
|-------------------------------------|--|
| <b>Status Indicators</b>            | Status, ID, SFP+ Port, QSFP28 Port<br>Status, Link, ACT, Fan Module, Power Supply Module |
| <b>Remote Management Protocol</b>   | SNMP V1/V2C/V3, CLI, Telnet  |
| <b>Power</b>                        |  |
| <b>Input Voltage</b>                | 90 to 264 V AC, 50-60Hz  |
| <b>Max. Power Consumption</b>       | 300W   |
| <b>Physical and Environmental</b>   |  |
| <b>Dimensions (HxWxD)</b>           | 1.73"x 17.4"x 16.5" (44x 442x 420mm)   |
| <b>Rack Space</b>                   | 1U   |
| <b>Fan Number</b>                   | 4 (3+1 Redundancy)   |
| <b>Hot-swappable Power Supplies</b> | 2 (1+1 Redundancy)   |
| <b>Airflow</b>                      | Front-to-Back  |
| <b>Weight</b>                       | 17.6 lbs (8kg), with 2 installed PSUs and 4 Fans   |
| <b>Operating Temperature</b>        | 32°F to 113°F (0°C to 45°C)  |
| <b>Storage Temperature</b>          | -40°F to 158°F (-40°C to 70°C)   |
| <b>Operating Humidity</b>           | 10% to 90% (Non-condensing)  |
| <b>Storage Humidity</b>             | 10% to 90% (Non-condensing)  |
| <b>Warranty</b>                     |  |
| <b>Warranty</b>                     | 5 Years  |

## FEATURES

| Functionality                   | Description                          |
|---------------------------------|--------------------------------------|
| <b>Layer 2 Protocols</b>        | IEEE802.3ae (10GBase)                |
|                                 | IEEE802.3ak                          |
|                                 | IEEE802.3an                          |
|                                 | IEEE802.3x                           |
|                                 | IEEE802.3ad (Link aggregation)       |
|                                 | IEEE802.1p                           |
|                                 | IEEE802.1Q                           |
|                                 | IEEE802.1D (STP)                     |
|                                 | IEEE802.1w (RSTP)                    |
|                                 | IEEE802.1s (MSTP)                    |
|                                 | IGMP Snooping                        |
|                                 | Jumbo Frame (9Kbytes)                |
|                                 | IEEE802.1ad (QinQ and flexible QinQ) |
|                                 | GVRP                                 |
| <b>Layer 3 Protocols (IPv4)</b> | BGP4                                 |
|                                 | OSPFv2                               |
|                                 | RIPv1                                |
|                                 | RIPv2                                |
|                                 | Policy-based routing                 |
|                                 | Route-policy                         |
|                                 | ECMP                                 |
|                                 | WCMP                                 |
|                                 | VRRP                                 |
|                                 | IGMP v1/v2/v3                        |
|                                 | PIM-SSM/SM/DM                        |
| <b>Basic IPv6 Protocols</b>     | ND                                   |
|                                 | ICMPv6                               |
|                                 | Path MTU Discovery                   |
|                                 | DNSv6                                |
|                                 | DHCPv6                               |
|                                 | ICMPv6                               |
|                                 | ICMPv6 redirection                   |
|                                 | ACLv6                                |
|                                 | TCP/UDP for IPv6                     |
|                                 | SNMP v6                              |
|                                 | Ping /Traceroute v6                  |
|                                 | IPv6 RADIUS                          |
|                                 | Telnet/SSH v6                        |

## FEATURES

| Functionality                       | Description   |
|-------------------------------------|---|
| <b>Basic IPv6 Protocols</b>         | FTP/TFTP v6<br>NTP v6<br>IPv6 MIB support for SNMP<br>VRRP for IPv6   |
| <b>IPv6 Features</b>                | Static routing<br>Policy-based routing<br>OSPFv3<br>RIPng<br>BGP4+<br>MLDv1/v2<br>PIM-SMv6<br>Manual tunnel<br>Auto tunnel<br>IPv4 over IPv6 tunnel<br>ISATAP tunnel  |
| <b>Data Center Network Features</b> | PFC, ECN, RDMA<br>VXLAN routing, VXLAN bridging<br>BGP-EVPN VXLAN   |
| <b>Visualization</b>                | Support gRPC communication protocol<br>Support sFlow sampling   |
| <b>QoS</b>                          | EXP priority mapping based on 802.1p, DSCP, TOS and IP Precedence<br>ACL traffic classification<br>Priority marking/remarking<br>Multiple queue scheduling mechanisms, such as SP, WRR, DRR, SP+WRR, and SP+DRR |
| <b>Stacking</b>                     | Stacking technology for virtualizing 2 devices into 1   |
| <b>Cache Management</b>             | Support cache state monitoring and management, identify traffic micro burst   |
| <b>Reliability</b>                  | GR for OSPF/IS-IS/BGP<br>BFD detection<br>RLDP (Rapid Link Detection Protocol)<br>1+1 power redundancy<br>3+1 fan redundancy<br>Hot-swappable fans and power modules  |
| <b>Security</b>                     | Network Foundation Protection Policy (NFPP)<br>CPU Protection (CPP)   |


## FEATURES

| Functionality          | Description  |
|------------------------|--|
| <b>Security</b>        | DoS protection<br>Detection of unauthorized data packets<br>Data encryption<br>RADIUS / TACACS+<br>Pv4 / IPv6 ACL packet filtering based on standard or extended VLANs<br>Plaintext authentication and MD5 cipher-text authentication of OSPF<br>Telnet login through limited IP addresses and the password mechanism<br>uRPF<br>Broadcast packet suppression<br>DHCP Snooping |
| <b>Manageability</b>   | SNMP v1/v2c/v3<br>Telnet<br>Console<br>Hardware support RCMI (combo interface for MGMT)<br>RMON<br>SSHv1/v2<br>FTP/TFTP for file upload and download management<br>NTP clock<br>Syslog<br>SPAN/RSPAN/ERSPAN<br>In-band Network Telemetry (INT)   |
| <b>Other Protocols</b> | DHCP Client<br>DHCP Relay<br>DHCP Server<br>DNS Client<br>ARP Proxy<br>Syslog  |
| <b>Power Supply</b>    | AC input:<br>Rated voltage range: 100-240V<br>Maximum voltage range: 90-264V<br>Frequency: 50-60Hz<br>Rated current: 7.2A-3.5A<br><br>HVDC input:<br>Input voltage range: 192-288V<br>Input current: 3.6A  |


## Accessories



Power Cord x2




Grounding Cable x1



Mounting Bracket x2




M4 Screw x14



M6 Screw x8



M6 Nut x8



Slide Rail x2



Inner Rail x2



 <https://www.fs.com>



The information in this document is subject to change without notice. FS has made all efforts to ensure the accuracy of the content, but all information in this document does not constitute any kind of warranty.